

Features

Engine	Perkins
Type	2206A-E13TAG2
Origin	UK
No. of Cylinders	6
Configuration	In-line
Cycle	4-stroke
Bore, mm	130
Stroke, mm	157
Displacement, l	12.5
Compression ratio	16.3:1
Aspiration	Turbocharged, air to air
Injection	Electric governor
Starting	24V Electric
Alternator, amps	24/12V

Alternator	Stamford
Type	HCI444E
Origin	UK
Construction	Single Bearing
Insulation system	Class "H"
Temperature rise, °C	125
Excitation	Self Excited
Voltage Regulator	A.V.R SX440
Protection	IP23
Rated power factor	0.8
Regulation	±1%
No. of Phases	3
No. of Poles	4
RPM	1500 1800
Frequency	50Hz 60Hz

Performances	1500rpm	1800rpm
Engine		
Efficiency		
Prime Power, KWm (hp)	305 (409)	349 (468)
Standby Power, KWm (hp)	349 (469)	381 (511)

Fuel system	1500rpm
Specific fuel consumption at:	
Prime Power, Litre/h	
50%	37.8 (10.0)
75%	55.0 (14.5)
100%	75.3 (19.9)



GENERATING SET POWERED BY PERKINS

SP350-GENSET

Circuit Breaker	3 Pole series MCCB adjustable, amps	600
	CT's	600/5
	Steel sheet enclosure with bolted cover (European origin, ABB or equivalent)	

Documentation	Engine instruction book-English
	Warranty and service book- Multi-language
	Alternator manual- English
	Wiring diagram

Dimensions and Weight	Length..... 2410 mm
	Width 1120 mm
	Height 1725 mm
	Weight Final weight and dimensions will depend on completed specification

Spare Parts Kit (Optional)	(Genuine Perkins)
Oil filter, full flow	
Oil filter, bypass	
Fuel filter	
Fuel filter water separator	
Coolant filter	
Air filter	
Fan belt set	
Alternator belt set	
Engine Oil	

International Standards	Engine conform to ISO 9001: 2000, ISO 14001, ISO10054, ISO 3046, BS 5514, DIN 6271.
	Alternator conform to ISO 9001, ISO 14001, BS EN 60034, BS 5000, VDE 0530, NEMA MG1-32, IEC34 CSA C22.2-100, AS 1359, BS 6861-1, B En 61000-6-2:2001.

Rating Guidelines
 PRIME POWER rating to ISO Standard Power for continuous operation. It is applicable for supplying electrical power at variable load with 70% load factor for an unlimited number of hours as opposed to commercially purchased power. A 10% overload capability for governing purpose is available for this rating.
 MAXIMUM STANDBY POWER rating corresponds to ISO Standard Fuel Stop Power. It is applicable for supplying standby electrical power at variable load in areas with well established electrical networks in the event of normal utility power failure. No overload capability is available for this rating.
 1 hp = 1KW x 1.36
 KWm = Kilo Watt mechanical, net with fan
 KWe = Kilo Watt electrical = KWm*gen.eff
 KVA = Kilo Volt Ampere calculations based based on 0.8 power factor = KWe/0.8

- Optional Equipment**
- Engine**
 - Water heater jacket
 - Oversize batteries
 - Extra fuel pre filter water separator
 - Alternator**
 - 12 wire reconnectable stator / Terminal arrangement
 - Upgrade to AVR MX321
 - Quadrature droop kit
 - Anti-condensation heater
 - Air inlet filters
 - General**
 - Upgrade to modular controller for paralleling.
 - Automatic transfer switch
 - Battery charger
 - Upgrade to 4 pole ACB
 - Fuel tank base frame integrated for 8 hours operation
 - Fuel tank separate with customized capacity and shape
 - Fuel level switch High / Low for alarm and control
 - Fuel transfer pump Automatic / Manual
 - Fuel tank air filter
 - Residential grade silencer
 - Weather protective and acoustic enclosure.